

## Sealing Ferrules & Wire

Our sealing ferrules & galvanised sealing wires are used in conjunction with pliers to **secure meters** & other small installations within **electricity, gas and utility** sectors, including requirements under the **MOCOPA framework**.

Ferrules are manufactured in **annealed copper** (tin-plated), and available in 6mm/12mm lengths. Sealing wire is produced from 0.93mm galvanised 7-strand steel, in pre-cut 15cm lengths as standard. Both items are packaged together as standard **in re-sealable bags of 100pcs** for ease of dispensing and use by field technicians (separated packaging also available on request).




### Applications

For use as a security seal on electric, gas, water and fuel meters. Suitable for MOCOPA applications.

### Size Guide


6mm / 12mm sealing ferrules (see below)

15cm galvanised 7-line sealing wire, 0.93mm (see below)



Sealing Ferrule Dimensions

D	Ø4mm
d	Ø2.1mm
L	6 / 12mm
tolerance ± 3%	



Sealing Wire Dimensions

### Material

Ferrules: Annealed copper, tin-plated /

Sealing Wire: Zinc-coated (galvanised) 7-strand steel wire (compliant to EN 10264-2)

### Customisation Options

6mm or 12mm size options

Our Ferrule Sealing Pliers can emboss upto 3-characters per side

### Standard Packaging

15,000pcs x 12mm ferrules & sealing wire / per carton

25kgs (24x40x22cm)